

1016
1016
4251744510164
Black Walnut A/B EGP foiled 19x1400x1210mm
19
1400
1210
Nuss amerik. ged. (Black Walnut)
A/B
DL
ca. 45-65mm fallend
einzeln foliert
Solid Wood panel for furniture, Black Walnut (Juglans nigra), A/B-DS1 (topside A
no sap, no knots / bottom side max. 20% sound sap permitted), EGP = long
lamella, widths of lamella ca. 45-65mm random, m.c. 8+/-2%, glued D4-EN 204,
sanded grit 100, single foiled, size 19x1400x1210mm
At the end of production, the wood moisture is approx. 8 +/- 2%, which
corresponds to the equilibrium moisture when used in closed rooms with a
healthy living climate of 20°C / 55% humidity
All solid wood panels / glued wood panels are glued formaldehyde-free using
tested German brand glues (e.g. Jowatt, Kleiberit) of stress classes D3 and D4 in
accordance with DIN/EN 204. Areas of application for these PVAc glues (=white
glues) are indoor areas with frequent short-term exposure to runoff water or
condensation and/or exposure to high humidity. As well as outdoor areas, but
protected from the weather. The glue content for solid wood panels is only
approx. 0.1%. The PVA glues used do not release any formaldehyde (in contrast,
chipboards are usually bound to formaldehyde resin and have a glue content of
up to 10%). With D3 gluing, only the technical class of solid wood panels
according to EN 13353 of SWP/1 (dry area according to EN 13986) can be
achieved. With D4 gluing, only the technical class of solid wood panels according
to EN 13353 of SWP/2 (wet area according to EN 13986) can be achieved.
All LARBON ® solid wood panels clearly exceed the necessary specifications of the
European standards DIN EN 13353 (technical requirements) and DIN EN 13017-2
(optical appearance classes).