

| Article No.         | 5567  |
|---------------------|---|
| EAN-Code            | 4251744555677   |
| Title               | Furniture panel Oak Rustik EGP foiled 30x2400x1210                                  |
| Thickness in mm     | 30  |
| Length in mm        | 2400  |
| Width in mm         | 1210  |
| Type of wood        | Wildeiche Möbelbauplatte  |
| Quality             | Wildeiche/Asteiche  |
| Type of lamella     | DL  |
| Width of lamella    | ca. 40-45mm fix   |
| Packaging / Foiling | einzeln foliert   |
| Description         | Solid Wood panels, Oak Rustik (topside no sap, Knots filled black both sides), long |
|                     | Lamella ca. 45mm fix, glued D4-EN 204, sanded grit 100, single foiled, size         |
|                     | 30x2400x1210 mm   |
| Wood moisture       | At the end of production, the wood moisture is approx. 8 +/- 2%, which              |
|                     | corresponds to the equilibrium moisture when used in closed rooms with a            |
|                     | healthy living climate of 20°C / 55% humidity                                       |
| Gluing              | All solid wood panels / glued wood panels are glued formaldehyde-free using         |
|                     | tested German brand glues (e.g. Jowatt, Kleiberit) of stress classes D3 and D4 in   |
|                     | accordance with DIN/EN 204. Areas of application for these PVAc glues (=white       |
|                     | glues) are indoor areas with frequent short-term exposure to runoff water or        |
|                     | condensation and/or exposure to high humidity. As well as outdoor areas, but        |
|                     | protected from the weather. The glue content for solid wood panels is only          |
|                     | approx. 0.1%. The PVA glues used do not release any formaldehyde (in contrast,      |
|                     | chipboards are usually bound to formaldehyde resin and have a glue content of       |
|                     | up to 10%). With D3 gluing, only the technical class of solid wood panels           |
|                     | according to EN 13353 of SWP/1 (dry area according to EN 13986) can be              |
|                     | achieved. With D4 gluing, only the technical class of solid wood panels according   |
|                     | to EN 13353 of SWP/2 (wet area according to EN 13986) can be achieved.              |
| DIN standard        | All LARBON ® solid wood panels clearly exceed the necessary specifications of the   |
|                     | European standards DIN EN 13353 (technical requirements) and DIN EN 13017-2         |
|                     | (optical appearance classes).   |